

## Bauder Bakor Hot Melt System

### Inverted Paved inc. JFRIPREMIUM+ Inverted Insulation

Hot liquid applied waterproofing system for use in Inverted and Cold Roof situations. Suitable in both New Build and Refurbishment situations. Can be used on various substrates and is ideal as a waterproofing beneath paved, ballasted, green and brown & biosolar & blue roof situations.

	Function	Product	Thickness	Weight	
1	Paving— 450x450x40mm on Bauder Pedestal Supports	Installed to achieve a permanent minimum load of 80kg/m <sup>2</sup> .	(min circa) 57mm	86kg/m <sup>2</sup>	
2	BauderJFRI WFRL	Vapour permeable polypropylene spun bonded membrane	0.45mm	0.1kg/m <sup>2</sup>	
3	BauderJFRI PREMIUM+ Insulation—Hard Landscape	High performance rigid expanded polystyrene insulation; lightweight, high compressive strength	185mm	5.55kg/m <sup>2</sup>	
4	AP1 Access	Fully bonded into the uppermost layer of the 790-11	1.5mm	1.8kg/m <sup>2</sup>	
5	790-11 Hot Melt Waterproofing	Hot applied, rubberised bitumen with Polyester Reinforcement layer for a monolithic fully bonded system.	6.2mm	6.5kg/m <sup>2</sup>	
			250.15mm	99.95kg/m <sup>2</sup>	

In-depth and up-to-date product specific technical data is available for each element within a system.  
Download from our website [bauder.co.uk/technical-centre](http://bauder.co.uk/technical-centre)

#### Characteristics of the system

- Monolithic waterproofing system—no laps
- 100% bond to deck surface
- Lasts the lifetime of the roof
- Safe2Torch compliant detailing on or near combustible construction materials.
- Prominent guarantee packages to meet project needs.

#### Accreditations and approvals



## Bauder Bakor Hot Melt System

### Inverted Paved inc. JFRIPREMIUM+ Inverted Insulation

System variations are available to the specifier so that a tailored solution meets the needs of the building. **The selection of products should be confirmed with our technical department to ensure suitability for the individual construction requirements of the flat roof.**

E: [technical@bauder.co.uk](mailto:technical@bauder.co.uk)

T: 01473 257671

#### OPTIONS AVAILABLE

In-depth and up-to-date product specific technical data is available for each component within a system. Download from our website [bauder.co.uk/technical-centre](http://bauder.co.uk/technical-centre)

Access/Protection Sheet alternatives	Thickness	Weight
BauderPLANT E 42	4.2mm	5.0kg/m <sup>2</sup>
K4E Charcoal Grey	4.2mm	5.6kg/m <sup>2</sup>
K4E Grey Slate	4.2mm	5.0kg/m <sup>2</sup>
K4E Brown	4.2mm	5.0kg/m <sup>2</sup>

Insulation to achieve 0.16 on a concrete deck	Thickness	Weight
BauderJFRI PREMIUM+	185mm	5.55kg/m <sup>2</sup>
BauderJFRI (300)	195mm	7.80kg/m <sup>2</sup>
BauderXPS (300)	220mm	6.60kg/m <sup>2</sup>
BauderGLAS Inverted	240mm	24.0kg/m <sup>2</sup>

#### System fire performance

The system arrangements tested, verified, and that achieve industry standards for fire performance are defined in the relevant Kiwa certificate. Please ensure you are aware of which permutations currently have a stated performance against fire by viewing and downloading the Kiwa certificate from our website [bauder.co.uk/technical-centre](http://bauder.co.uk/technical-centre)

Bauder continually tests its systems for fire performance and so if the permutation of products you are specifying is not stated in our latest Kiwa certificate, please contact [technical@bauder.co.uk](mailto:technical@bauder.co.uk) for clarification.