


TECHNICAL DATA SHEET

BauderJFRI (500) Inverted Insulation

Product Description Rigid expanded polystyrene (EPS). Has a higher compressive strength than the BauderJFRI (200), BauderJFRI (300) and BauderJFRI (200) HP grade. This product is rebated on all four sides to ensure thermal continuity.



Application Fields This product is for use within inverted (protected membrane) roof systems and can be laid directly onto Bauder Hot Melt and Bauder bitumen-based Waterproofing Membranes. Contact Bauder Technical for advice relating to other membrane types.

Use in conjunction with BauderJFRI WFL Membrane prior to installing paving, decking or ballast or Extensive, Brown, Biodiverse, Intensive Green, biosolar and Blue Roofs.

Use in conjunction with BauderXPS or BauderROCK NC 56mm Upstand Board to exposed vertical upstands.

For a comprehensive specification contact Bauder technical department.

PRODUCT INFORMATION AND TECHNICAL PERFORMANCE

Characteristic	Test Method	Unit	Value
Dimensions			
Width	BS EN 822	mm	1215 (including 15 rebate)
Length	BS EN 822	mm	1215 (including 15 rebate)
Coverage		m ²	1.44
Single thickness	BS EN 823	mm	100 to 240mm in 5mm increments (non-standard thicknesses available as a special order)
Typical density	BS EN 1602	kg/m ³	55
Thermal Conductivity			
Declared thermal conductivity	BS EN 13164	W/mK	0.033
Design thermal conductivity	BS EN 13163	W/mK	0.038
Mechanical Properties			
Compressive strength	BS EN 826	N/mm ²	0.50 with 10% nominal compression
Compressive creep	BS EN 1606	N/mm ²	0.15 with 2% compression
Compressive strength for permanently sited loads. Contact Bauder Ltd where plant/equipment is to be sited on top of the Bauder system.			
Moisture Properties			
Long term water absorption by immersion	BS EN 12087		≤1%
Long term water absorption by diffusion	BS EN 12088		≤1%
Fire Properties			
Reaction to fire - classification to	BS EN 13501-1		Euroclass E
Properties in relation to fire	European Commission Directive 2000/553/EC		Unrestricted with stone, screed, or paving cover

TECHNICAL DATA SHEET

SURFACE FINISH	
Top	Un-faced
Bottom	Un-faced
Colour	White
Board edge	Rebated

CERTIFICATION AND ENVIRONMENTAL INFORMATION	
BBA Certificate	-
Environmental Product Declaration (EPD)	BREG EN EPD No: 000395 Issue 01
Declaration of Performance (DoP)	13189450
Declaration of Conformity (DoC)	-
International Standards Organisation (ISO)	ISO 9001:2015 Quality Management Certificates GB2005746 (UK) ISO 14001:2015 Environmental Management Certificates EM2001097(UK)
BRE Green Guide generic product rating	A (www.bre.co.uk/greenguide element number 1315320001)
Ozone depletion potential (ODP)	Zero
Global Warming Potential (GWP)	<5 kg CO ₂ Eq./kg
Recyclability	100%

INSTALLATION GUIDANCE
<ol style="list-style-type: none"> 1. BauderJFRI (500) inverted roof insulation is installed loose laid over the weatherproofing, ensuring all overlap joints are tightly butted together. 2. Boards are laid in a staggered pattern starting from the point of access to the roof, when using a second layer stagger joints of insulation from first layer. 3. Only install amount of BauderJFRI (500) insulation that can be ballasted, paved, or green roof installed in the same day. 4. BauderJFRI (500) Inverted Roof Insulation should always have a BauderJFRI WFRL (Water Flow Reducing Layer) loose laid to its upper surface. 5. Cutting should be carried out either by using a fine-toothed saw, a hot wire system or by scoring with a sharp knife and snapping the board over a straight edge. 6. Ensure accurate trimming to achieve close-butting joints and continuity of insulation. 7. BauderJFRI WFRL (Water Flow Reducing Layer) is loose laid over the insulation running across the fall of the roof with 300mm overlaps. The membrane is turned up at all roof penetrations and upstands to a height to ensure it finishes above the top level of the ballast or paving. 8. Upstands can be finished using BauderXPS Upstand Boards, BauderROCK NC 56mm or BauderGLAS Inverted Upstand Board (fixing depends on height of upstand) to reduce the risk of cold bridging. Please refer to Technical Data Sheets for limitations of use. 9. Fixing instructions for Upstand Boards can be found on the relevant Technical Data Sheet.

TECHNICAL DATA SHEET

TRANSPORT

BauderJFRI Insulation is transported direct to site from the manufacturer on artic curtain sided vehicles with no offload facility. Smaller specialist vehicles such as rigid/moffett/flat bed/pump truck & tail lift are available.

Due to the weight of this material all insulation must be offloaded via a forklift or crane and cannot be handballed.

PRODUCT STORAGE GUIDANCE

BauderJFRI Insulation should be stored outside and stacked clear of the ground and covered with a pale pigmented polythene sheet or weatherproof tarpaulin.

BauderJFRI Insulation should not be left in the sun covered by either a transparent or a dark plastic sheet, since in both cases, board temperatures can build up to a level hot enough to appreciably alter their dimensions or warp them.

Care must be taken to avoid contact with solvents and materials containing organic components.

Boards contain a flame-retardant additive to inhibit accidental ignition from small fire sources, it is combustible and should not be exposed to open flame or other ignition sources.

Damaged boards must not be used.

PACKS/PACKAGING MATERIAL

BauderJFRI (500) boards are shrink wrapped in polythene and delivered to site 2 packs high on timber pallets. Each pack is 1.2 x 1.2 x 1.2m.

Height of pallet with 2 packs varies between 2.4 and 2.72m depending on board thickness.

HANDLING/PPE

All persons using this product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using this product, installers should be provided with, and wear, suitable personal protective equipment.

There are no requirements for special PPE when installing or cutting the insulation panels. BauderJFRI (500) insulation is non-toxic and not irritating to the eyes or skin.

SHELF LIFE

When stored correctly, the product has no stated shelf life.

DISPOSAL GUIDANCE

Off-cuts need to be disposed via an authorised disposal contractor to an approved waste disposal site, observing all relevant regulations. (European waste catalogue EWC number 17 06 04 "Insulation material").

RE-USE OPTIONS OF PRODUCT

BauderJFRI (500) is 100% recyclable.

Please refer to EPD in Certification and Environmental information section. Document can be found at www.bauder.co.uk

FURTHER INFORMATION/DOCUMENTS

Current documents such as brochures, installation guides, etc can be found by visiting www.bauder.co.uk

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.



Can be found via the website