

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name **Bauder LiquiPRIME 2 - 10 kg**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses concrete priming

Recommended restrictions Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company designation Bauder Ltd.
70 Landseer Road
Ipswich IP3 0DH
Telephone: +44 (0)1473 257671

E-mail (competent person) info@bauder.co.uk

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only).

For medical advice, members of the public should contact NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

* Classification according to Regulation (EC) No. 1272/2008 Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

2.2 Label elements

Hazard pictogram



GHS02



GHS07

Signal word

Danger

* Hazardous component(s) to be indicated on label

methyl methacrylate , 1.4-Butandiol dimethacrylate , ethyl methacrylate

* H-statement(s)

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

* P-statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P312: Call a POISON CENTER/doctor if you feel unwell.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization

Polymers dissolved in methyl methacrylate

Hazardous ingredients

Ingredient	Numbers	Classification (EC) 1272/2008	Concentration
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6REACH No.: 01-2119452498-28-XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1;H317	55.0 - 60.0 % by weight
1,4-Butandiol dimethacrylate	CAS No.: 2082-81-7 EC-No.: 218-218-1REACH No.: 01-2119967415-30-XXXX	Skin Sens. 1; H317	1.0 - 5.0 % by weight
1,1'-(p-Tolylimino)dipropyl-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1REACH No.: 01-2119980937-17-XXXX	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight
ethyl methacrylate	CAS No.: 97-63-2 EC-No.: 202-597-5 Index-No.: 607-071-00-2REACH No.: 01-2119490215-40-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1; H317	0.1 - 1.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area. Take off all contaminated clothing immediately. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.

If inhaled

Move to fresh air. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

In case of skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation occurs, seek medical advice/attention.

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

In case of eye contact

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed

Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Water spray, Dry powder

Extinguishing media which must not be used for safety reasons

High volume water jet

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Hazardous decomposition products formed under fire conditions. Violent polymerization may be caused by: Extremes of temperature and direct sunlight.

5.3 Advice for firefighters

Special protective equipment for firefighting

In the event of fire, wear self-contained breathing apparatus.

Additional information on firefighting

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from firefighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment.

Ensure adequate ventilation. Vapours are heavier than air and may spread along floors.

6.2 Environmental precautions

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean contaminated surface thoroughly.

6.5 Additional information

Other information

Treat recovered material as described in the section "Disposal considerations".

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	Handle and open container with care. Avoid contact with skin and eyes. Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty container away from heat and sources of ignition.
Precautions	Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Observe label precautions.
Advice on protection against fire and explosion	Take precautionary measures against static discharges. Vapours may form explosive mixture with air. Use water spray to cool unopened containers.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container requirements	Keep in properly labelled containers. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in a cool, well-ventilated place.
TRGS 510	3
Recommended storage temperature	Keep in a dry, cool place.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

methyl methacrylate

Great Britain				
Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value / ppm	Short-term exposure value / mg/m ³	Source
50	208	100	416	EH40/2005 Workplace exposure limits (2011)

Europe			
Long-term exposure value/ ppm	Short-term exposure value / ppm	Issuing date	Source
50	100	2009/161	DIRECTIVE 2009/161/EU

DNEL	Target group	Exposure route	Exposure frequency	Source
210 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
210 mg/m ³	Workers	Inhalation	Long term effects systemic	Company data
1,5 mg/cm ²	Workers	Skin	Long term effects Local	Company data
13,67 mg/kg	Workers	Skin	Long term effects systemic	Company data
105 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

74,3 mg/m ³	Consumers	Inhalation	Long term effects, systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Long term effects Local	Company data
8,2 mg/kg	Consumers	Skin	Long term effects systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Short-term effects Local	Company data

PNEC	Exposure route	Source
0,94 mg/l	freshwater	Company data
0,094 mg/l	marine water	Company data
5,74 mg/kg	sediment	Company data
1,47 mg/kg	Soil	Company data

1.4-Butandioldimethacrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
14,5 mg/m ³	Workers	Inhalation	Long term effects systemic	Company data
4,2 mg/kg	Workers	dermal exposure	Long term effects systemic	Company data

1,1`-(p-Tolylimino)dipropan-2-ol

DNEL	Target group	Exposure route	Exposure frequency	Source
2 mg/m ³	Workers	Inhalation	Long term effects	Company data
0,6 mg/kg	Workers	Skin	Long term effects	Company data

PNEC	Exposure route	Source
199,5 mg/l	Waste water treatment	Company data
0,0072 mg/kg	marine water	Company data
0,017 mg/l	freshwater	Company data

8.2 Exposure controls

Respiratory protection

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Remarks

Recommended Filter type: A1, A2 (in case of higher concentration)

Hand protection

Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Unsuitable material

woven fabric, Leather gloves

Suitable material

Nitrile

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

Eye protection	Tightly fitting safety goggles
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and at the end of workday. Use protective skin cream before handling the product. Avoid contact with the skin and the eyes.
Engineering measures	Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	Liquid
Colour	yellow-brown
Odour	smell of Methylmethacrylate
pH	not applicable
Melting point [°C] / Freezing point[°C]	not determined
Boiling point [°C]	> 100 °C
Flash point [°C]	10 °C
Evaporation rate [kg/(s m²)]	not determined
Explosion limits [Vol-%]	The product itself has not been tested. methyl methacrylate
Lower limit	1,7 vol. %
Upper limit	12,5 vol. %
Vapour pressure [kPa]	> 50 hPa
Vapour density	not determined
Density [g/cm³]	1,05 g/cm³
Temperature [°C]	20 °C
Water solubility [g/l]	
Remarks	insoluble
Partition coefficient n-octanol /water (log P O/W)	not determined
Autoignition temperature [°C]	not determined

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

Explosive properties Not relevant
In use, may form flammable/explosive vapour-air mixture.

Oxidising properties Not relevant

9.2 Other information

Ignition temperature [°C] not determined

* Flow time [s] 40 sec

Temperature [°C] 20 °C

Measuring method DIN cup 6 mm

SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution. Risk of receptacle bursting.

10.4 Conditions to avoid

Conditions to avoid Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid Reacts violently with peroxides. Reducing agents, Strong bases, Amines, Oxidizing agents

SECTION 11: Toxicological information

11.1 Information on toxicological effects

*Oral toxicity [mg/kg]

Hazardous ingredients

*methyl methacrylate				
Value	Test criterion	Test species	Measuring method	Source
>5001 mg/kg	LD50	rat	OECD Test Guideline 401	Company data

1.4-Butandioldimethacrylate				
Value	Test criterion	Test species	Measuring method	Source
>5000 mg/kg	LD50	rat	OECD Test Guideline 401	Company data

*1,1'-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Measuring method	Source
26 mg/kg	LD50	rat	OECD Test Guideline 423	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

*Dermal toxicity [mg/kg]

Hazardous ingredients

*methyl methacrylate			
Value	Test criterion	Test species	Source
>5001 mg/kg	LD50	rabbit	Company data

1.4-Butandioldimethacrylate				
Value	Test criterion	Test species	Remarks	Source
>3000 mg/kg	LD50	rabbit	* 1)	Company data

* 1): The information is based on our own tests, on data from literature and information from protective glove producers or is based on data obtained from similar substances.

1,1`-(p-Tolylimino)dipropan-2-ol			
Value	Test criterion	Test species	Source
2001 mg/kg	LD50	rat	Company data

LC50 Inhalation 4h for vapours [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test criterion	Test species	Source
29,8 mg/l	LC50	rat	Company data

Irritant effect on skin

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
irritating	rabbit	Company data

1.4-Butandioldimethacrylate	
Value	Source
No skin irritation	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No skin irritation	Company data

Irritant effect on eyes

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
Irritant	rabbit	Company data

1.4-Butandioldimethacrylate	
Value	Source
No eye irritation	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Irritant	Company data

Sensitization

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
Skin sensitization	mouse	Company data

1.4-Butandioldimethacrylate		
Value	Test species	Source
sensitizing	mouse	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No sensitization responses were observed.	Company data

Carcinogenic effects

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
not a carcinogen	rat, mouse	Company data

1.4-Butandioldimethacrylate	
Value	Source
No known effect.	Company data

Mutagenicity

Hazardous ingredients

methyl methacrylate	
Value	Source
not mutagenic	Company data

1.4-Butandioldimethacrylate	
Value	Source
No known effect.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
negative	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

Reproduction toxicity

Hazardous ingredients

methyl methacrylate	
Value	Source
not toxic to reproduction	Company data

1.4-Butandioldimethacrylate	
Value	Source
No known effect.	Company data

Specific target organ toxicity (single exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
Causes respiratory tract irritation.	Company data

1.4-Butandioldimethacrylate	
Value	Source
No known effect.	Company data

Specific target organ toxicity (repeated exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
No known effect.	Company data

1.4-Butandioldimethacrylate	
Value	Source
No known effect.	Company data

11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Irritating to eyes, respiratory system and skin. Irritating to mucous membranes

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

Hazardous ingredients

methyl methacrylate					
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source
191 mg/l	LC50	On-corhynchus mykiss (rainbow trout)	OECD Test Guideline203	96 h	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

1.4-Butandioldimethacrylate				
Value	Test criterion	Test species	Exposure duration [h]	Source
32,5 mg/l	LC50	Leuciscus idus (Golden orfe)	48 h	Company data

1,1'-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure duration [h]	Source
17 mg/l	LC50	Brachydanio rerio (zebra fish)	96 h	Company data

Toxicity to daphnia [mg/l]

Hazardous ingredients

methyl methacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
69 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data

1.4-Butandioldimethacrylate				
Value	Test criterion	Test species	Exposure duration [h]	Source
7,51 mg/l	EC10	Daphnia magna (Water flea)	21 day(s)	Company data

1,1'-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure duration [h]	Source
28,8 mg/l	EC50	Daphnia magna (Water flea)	18 h	Company data

Toxicity to algae [mg/l]

Hazardous ingredients

methyl methacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
>110 mg/l	EC50	Selenastrum capricornutum (green algae)	72 h	OECD Test Guideline201	Company data

1.4-Butandioldimethacrylate				
Value	Test criterion	Test species	Exposure duration [h]	Source
9,79 mg/l	EC50	Desmodesmus subspicatus	72 h	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

1,1'-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure duration [h]	Source
245 mg/l	EC50	Desmodemus subspicatus	27 h	Company data

NOEC (fish) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
9,4 mg/l	Brachydanio rerio (zebra fish)	OECD Test Guideline 210	Company data

NOEC (daphnia) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
37 mg/l	Daphnia magna (Water flea)	OECD Test Guideline 202	Company data

12.2 Persistence and degradability

Biodegradability

Hazardous ingredients

methyl methacrylate		
Value	Method of analysis	Source
Readily biodegradable.	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	Company data

1.4-Butandioldimethacrylate		
Value	Remarks	Source
Biologisch abbaubar.84 %	Angabe des Herstellers	Company data

1,1'-(p-Tolylimino)dipropan-2-ol	
Value	Source
Poorly biodegradable.	Company data

12.3 Bioaccumulative potential

Bioaccumulation

Hazardous ingredients

methyl methacrylate	
Value	Source
Does not bioaccumulate.	Company data

1.4-Butandioldimethacrylate

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

Value	Source
Does not bioaccumulate.	Company data

1,1'-(p-Tolylimino)dipropan-2-ol	
Value	Source
no data available	Company data

12.4 Mobility in soil

Mobility

Hazardous ingredients

methyl methacrylate	
Mobility	Source
Terrestrial Compartment Not relevant	Company data

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination

Hazardous ingredients

methyl methacrylate	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

1.4-Butandioldimethacrylate	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

1,1'-(p-Tolylimino)dipropan-2-ol	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

12.6 Other adverse effects

Further information on ecology

We have no quantitative data concerning the ecological effects of this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The following Waste Codes are only suggestions:

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en






Replaces version from: 13.05.2019

Print date: 14.03.2022

Waste Code 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned empty packaging Empty containers should be taken for local recycling or waste disposal. Dispose of in accordance with local regulations.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.2 Description of the goods	PAINT	PAINT	PAINT
UN proper shipping name		PAINT	Paint
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group	II	II	II
Labels	3 	3 	3 
Risk No.	33		
Category	2		
Factor	3		
Classification Code	F1		
SP 640	640D		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		B	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC Code Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations Additionally, observe any national regulations!

Classification in compliance with the Industrial Safety Regulation highly flammable

GISCODE RMA15

MAL-Code 4-5

SECTION 16: Other information

Modifications since last version Modifications of the previous version are denoted with an asterisk (*).

Relevant H-phrases
H225: Highly flammable liquid and vapour.
H300: Fatal if swallowed.
H315: Causes skin irritation.

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: Bauder LiquiPRIME 2 - 10 kg

Article-No.: GB81001020

Revision Date: 14.03.2022

Version: 3.0/en



Replaces version from: 13.05.2019

Print date: 14.03.2022

Wording of the hazard classes

H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H412: Harmful to aquatic life with long lasting effects.

Flam. Liq.: Flammable liquid
STOT SE: Specific target organ toxicity - single exposure
Skin Irrit.: Skin irritation
Skin Sens.: Skin sensitization
Acute Tox.: Acute toxicity
Eye Irrit.: Serious eye irritation
Aquatic Chronic: Hazardous to the aquatic environment

* Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Flam. Liq. 2; H225	Calculated
Skin Irrit. 2; H315	Calculated
Skin Sens. 1; H317	Calculated
STOT SE 3; H335	Calculated

Recommended restrictions Reserved for industrial and professional use.

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.