

# Technical data sheet

## BauderPVC DP 25

### Decor profile



V3 22/11/2022

<b>Product description</b>	Bauder Décor PVC profile simulates the visuals of a standing seam metal profile.
<b>Application fields</b>	Suitable with all BauderTHERMOFOL membranes.
<b>Colour</b>	anthracite RAL 7016
<b>Article number</b>	6025 4000



Characteristic	Unit	Value
<b>Visible defects</b>	-	no visible defects
<b>Length</b>	m	3,0
<b>Width</b>	mm	35
<b>Height</b>	mm	25
<b>Processing</b>	-	Hot air welding with approx. 470 °C
<b>Material</b>	-	PVC-P
<b>Overall thickness</b>	mm	2,0
<b>External fire performance</b>	-	not applicable

<b>Installation guidance</b>	Décor profile is heat welded onto the PVC membrane at 470°C with a hot air welding gun. Before installation begins, clean the membrane with Bauder PVC cleaner and mark the profile centre spacing on the field sheet membrane with a chalk line.
<b>Handling/PPE</b>	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using/handling the product, installers should be provided with, and wear, suitable personal protective equipment.
<b>Further information/documents</b>	Current documents such as DoC's, DoP's (where relevant), brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>
<b>Safety Data Sheet</b>	Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.