

Bauder PMMA Cleaner

V3 04.10.2022

Product description	Bauder PMMA Cleaner is used with the Bauder LiquiTEC roofing and balcony PMMA products.
Application fields	It is used to pre-treat substrates and to degrease metal when overcoating or if work is interrupted. It can also be used to clean tools.



Article Number GB81007010

Characteristic	Unit	Value
Gross weight	kg	8.85
Pack size	litre	9
Colour		Transparent
Coverage	litre/m ²	0.2 Depending on the degree of soiling and the type of substrate. Consumption based on a smooth non-absorbent surface
Base		ethyl acetate
Drying time at 20°C*	minutes	20 approx.
Overcoat time at 20°C*	minutes	20 to 60 Ensure surface is dry before overcoating
Shelf life unopened	months	12

*Times will be slightly increased at lower temperatures and slightly reduced at higher temperatures.

Storage guidance	Store unopened in a cool, dry, well-ventilated place above freezing, out of direct sunlight and in the original container.
Packaging material	The product is packaged in tin plate rectangular steel tin with a polypropylene berg closure. Weight of packaging approximately 0.983 kg.
Handling/PPE	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.
Emptying and disposal guidance	Containers which have been emptied, but not washed out in line with the specific methods and calculations prescribed in WP1 and WM3, should be classified as packaging containing residues of/or contaminated by hazardous substances using waste code 15-01-10. Containers with hazardous residues that have been emptied and washed-out in line with the method and calculations which are detailed in the industry guidance can be classified as non-hazardous waste packaging.
Further information/ documents	Current documents such as brochures, installation guides, etc. can be found by visiting www.bauder.co.uk
International Standards Organisation (ISO)	ISO 9001:2015 Quality Management Certificate DEKRA 80408283 ISO 14001:2015 Environmental Management Certificate DEKRA 170408038

Technical data sheet



Installation Guidance

Installation is to be carried out by Bauder Approved Contractors in accordance with the specification and guidelines. Please consult the Bauder technical department.

Substrate assessment / pre-treatment / preparation

Ensure that the substrate is clean, dry, and free from dust, grease, oil, and any other contamination.

The substrate must be assessed, treated, and prepared in accordance with the Bauder project specification.

Application

Where waterproofing and coating work is interrupted for more than 12 hours, the lap must be treated with PMMA Cleaner.

Wearing the appropriate personal protective equipment, pour onto a clean cloth and apply an even layer by wiping the surface to remove any contamination. Regularly replace the cloth. Large areas can be treated by mopping.

Tool Cleaning

Decant the cleaner into a suitable clean receptacle. Clean tools with PMMA Cleaner immediately after use. Merely placing tools in the cleaner will not prevent hardening.

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as a substance/mixture; therefore, this product does have a requirement for a Safety Data Sheet.
