

## Bauder Catalyst

V3 04.10.2022

<b>Product description</b>	Bauder Catalyst is a powdered hardener for Bauder LiquiTEC PMMA products. Refer to the individual LiquiTEC product's technical data sheet for specific requirements.
<b>Application fields</b>	Bauder Catalyst is used in Bauder LiquiTEC PMMA cold applied liquid roofing and balcony systems.



<b>Article Number</b>	GB81005010 – 25kg GB81005025 – 1kg GB81005030 – 0.1kg
-----------------------	---

Characteristic	Unit	Value
<b>Gross Weight</b>		
25 kg	kg	26.3
1 kg		1.1
0.1 kg		0.15
<b>Pack size</b>	kg	25kg box 1kg bag 0.1kg (100g) bag
<b>Colour</b>		White
<b>Base</b>		dibenzoyl peroxide
<b>Shelf life unopened</b>	months	12

<b>Storage guidance</b>	Store in a closed container protected from contamination and in a dry place away from sources of ignition and heat at temperatures below +25°C. Protect from direct sunlight.
<b>Packaging material</b>	Weight of packaging is approximately 0.1 kg bag – 0.05 kg low density polyethylene bag 1 kg bag – 0.1 kg low density polyethylene bag 25kg box – 0.3 kg low density polyethylene liner, 1 kg cardboard box.
<b>Handling/PPE</b>	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.
<b>Emptying and disposal guidance</b>	Containers which have been emptied, but not washed out in line with the specific methods and calculations prescribed in WP1 and WM3, should be classified as packaging containing residues of/or contaminated by hazardous substances using waste code 15-01-10. Containers with hazardous residues that have been emptied and washed-out in line with the method and calculations which are detailed in the industry guidance can be classified as non-hazardous waste packaging.
<b>Further information/ documents</b>	Current documents such as brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>

### International Standards Organisation (ISO)

ISO 9001:2015 Quality Management  
Certificate DEKRA 80408283

ISO 14001:2015 Environmental Management  
Certificate DEKRA 170408038

# Technical data sheet



## Installation Guidance

Installation is to be carried out by Bauder Approved Contractors in accordance with the specification and guidelines. Please consult the Bauder technical department.

## Use

Refer to the relevant LiquiTEC PMMA product technical data sheet.

Pour the required amount into the Bauder LiquiTEC resin and mix in accordance with technical data sheet.

Note: Ensure catalyst is fully dissolved in the resin before application.

**Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as a substance/mixture; therefore, this product does have a requirement for a Safety Data Sheet.**

---