

# Technical data sheet

## BauderPIR T G

### Tapered insulation



V5 09/12/2022

<b>Product description</b>	Rigid polyurethane foam board un-faced on both sides. The side features a number and arrow to indicate board size and which way up the board should be laid.		
<b>Application fields</b>	Thermal insulation with a low thermal conductivity to provide falls on a roof, for use within Bauder warm roof systems.		
<b>Article number</b>	9611 0033		
<b>Facing</b>	top:	Un-faced	
	bottom:	Un-faced	
<b>Board edge</b>	Square (not rebated)		
<b>Description</b>	PU-EN13165-T2-DS(70,90)3-DS(-20,-)2-CS(10\Y)120-TR100		

Characteristic	Test method	Unit	Value
<b>Length</b>	EN 822	mm	1200
<b>Width</b>	EN 822	mm	800
<b>Thickness</b>	EN 823	mm	20 - 400
<b>Gradients</b>	-	-	1:33, 1:40, 1:50, 1:60, 1:67, 1:80
<b>Reaction to fire</b>	EN 13501 - 1	Class	E
<b>Compressive Strength 10% compression</b>	EN 826	-	0.12 N/mm <sup>2</sup> 120 kPa 12,000 kg/m <sup>2</sup>
<b>Thermal conductivity (λ<sub>D</sub>) - (EU)</b>	EN 13165	W/mK	0,026 < 80 mm 0,025 80 mm -<120 mm 0,024 > 120 mm
<b>Water absorption</b>	EN 12087	Vol%	max. 3
<b>PIR Index</b>	-	-	> 250

**Maximum loading for permanently sited loads**

When equipment/plant is to be located on the finished roof a maximum permanent load of 2,400Kg/m<sup>2</sup> (24 kPa) (24KN/m<sup>2</sup>) can be supported with a 2% compression expected. Please refer to the Bauder Installation Guide and project specification for installation guidance.

**Product storage guidance**

Thermal insulation has to be transported and stored protected from moisture, open flames and direct sunlight. All insulation boards must be kept dry, on pallets and off the ground. The packaging of Bauder Insulation products should not be considered adequate for outside protection. If outside storage cannot be avoided the boards should be stacked clear of the ground and covered with an opaque polythene sheet or weatherproof tarpaulin.

**Packaging material**

The product will be delivered on EPS skids or wooden pallets with polythene overwrap (30% re-cycled content) to protect the product.

**Handling/PPE**

All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear,



Notified body: FIW München, 0751  
EN 13165



# Technical data sheet

## BauderPIR T G

### Tapered insulation



	suitable personal protective equipment.
<b>Shelf life</b>	When stored correctly, the product has no stated shelf life.
<b>Disposal guidance</b>	Rigid polyurethane foam waste can be disposed of with household waste or commercial waste similar to household waste (European waste catalogue EWC number 170604 "Insulation material").
<b>Re-use options of product</b>	Please refer to EPD stated below in Certification and environmental information.
<b>Further information/documents</b>	Current documents such as DoC's, DoP's (where relevant), brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>
<b>Certification and environmental information</b>	<p><b>BBA Certificate No.:</b> 16/5365</p> <p><b>Environmental Product Declaration:</b> EPD-IVP-20160147-IBE1-EN</p> <p><b>International Standards Organisation (ISO):</b> ISO 9001:2015 Quality Management Certificates EN1271 (UK) and 70499/03-15_e (Germany)</p> <p>ISO 14001:2015 Environmental Management Certificates A10552 (UK) and 70499/03-15_d (Germany)</p> <p>ISO 50001: 2011 Energy Management Certificate 70499/03-15_c (Germany)</p> <p><b>Ozone depletion potential (ODP)</b> Zero</p>
<b>Safety Data Sheet</b>	Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.



Notified body: FIW München, 0751  
EN 13165

