

Liquid Thixo

V4 04.10.2022

Product description	Used as a liquid thickening / thixotropic agent for addition to certain Bauder LiquiTEC PMMA products.
Application fields	Liquid Thixo is used in Bauder PMMA primers and LiquiFINISH for upstand details in excess of 250mm high and sloping areas.



Article Number GB81002500

Characteristic	Unit	Value
Gross weight	kg	1.52
Net weight	kg	1.5
Pack size	litre	0.5
Colour		Translucent brown liquid
Base		Solution of modified carbamide
Shelf life unopened	months	12

Storage guidance	Store unopened in a cool, dry, well-ventilated place above freezing, out of direct sunlight and in the original container.
Packaging material	The product is packaged in tin plate steel screw top tin. Weight of packaging approximately 0.76 kg.
Handling/PPE	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.
Emptying and disposal guidance	Containers which have been emptied, but not washed out in line with the specific methods and calculations prescribed in WP1 and WM3, should be classified as packaging containing residues of/or contaminated by hazardous substances using waste code 15-01-10. Containers with hazardous residues that have been emptied and washed-out in line with the method and calculations which are detailed in the industry guidance can be classified as non-hazardous waste packaging.
Further information/ documents	Current documents such as brochures, installation guides, etc. can be found by visiting www.bauder.co.uk
International Standards Organisation (ISO)	ISO 9001:2015 Quality Management Certificate DEKRA 80408283 ISO 14001:2015 Environmental Management Certificate DEKRA 170408038

Technical data sheet



Installation Guidance

Installation is to be carried out by Bauder Approved Contractors in accordance with the specification and guidelines. Please consult the Bauder technical department.

Substrate assessment / pre-treatment / preparation

Ensure that the substrate is clean, dry, and free from dust, grease, oil, and any other contamination.

The substrate must be assessed, treated, and prepared in accordance with the Bauder project specification.

Initial mixing / decanting

Thoroughly mix the resin in the drum with a slow speed mixer until the resin achieves a uniform consistency.

If required to decant, mix in the drum before decanting a measured weight into a suitable container.

Mixing

Up to 2% by weight depending on desired thixotropy. Refer to the relevant LiquiTEC PMMA product Technical Data Sheet.

Evenly mix the Liquid Thixo into the PMMA base resin.

Leave to stand for approximately 2-5 minutes for thixotropy to develop.

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as a substance/mixture; therefore, this product does have a requirement for a Safety Data Sheet.
